SPECIFICATIONS

		KS20			
	Te	chnical Key Spec	ification		
Print Heads		Japanese Konica Minolta Head KM1024i (13pL)			
PHILL HEADS		KS-2045	5	KS-2085	
		4 Head		8 Head	
		Media Specifica	tion		
	Width	3300 mm (129 in)			
Thickness		Maximum 3.0 mm (120 mil) with Liner (flexible)			
	Roll Outer Diameter	Maximum 352 mm (14.08 inch), 50.8 (2 in)			
Media	Roll Weight	Maximum 150 kgs			
	Core Diameter	76.2 mm (3 in)			
Media Types		Vinyl, Flex, PVC Banner, Polyster Fabric, Backlite Film, Fabric (Eco-Solvent Base) Window			
		Film, PE Media			
Media Heating System		Pre-heater and post-heater, setting range for the preset temprature: 30 to 60°C. Dryer setting range for the preset temperature: 30 to 60°C			
		Print Specificati	ons		
Printing Width		Maximum 3200mm (126 inch.)			
Printing Resolution (dots per inch)		Maximum up to 1440 dpi			
Connectivity		High Speed USB			
		Ink Specification	ons		
Ink Types		Mild Solvent Ink			
Ink Colors		4 Color 8 Color			
	Power Cor	nsumption & Worki	ng Environment		
Power Requirements		AC 220 V ±10%, 20 Amps, 50/60 Hz			
Power ON		Temperature: 18 to 28°C Humidity: 20 to 80%RH (non-condensing)			
Power OFF		Temperature: 5 to 40°C Humidity: 20 to 80%RH (non-condensing)			
		Machine Meaurm			
Printer Dimension	S		4955mm x 945mm x 15'	75mm (LxWxH)	
Weight (approx. with stand)		1500 kgs			
		Performance			
Print Mode		Passes	Speed - 4 Head	Speed - 8 Head	DPI
Mode 1		2P	1175 SQFT/HR	2056 SQFT/HR	540*720
Mode 2		3P	785 SQFT/HR	1374 SQFT/HR	540*1080
Mode 3		4P	495 SQFT/HR	866 SQFT/HR	540*1440
Mode 4		6P	410 SQFT/HR	718 SQFT/HR	540*1080
Mode 5		8P	280 SQFT/HR	490 SQFT/HR	540*1440

Kaleido KS-20 is highly eco-friendly and is based on KDS' Greentech. Greentech printing technology enables printing with **environment-friendly** mild-solvent inks. It ensures low chemical emissions to reduce environmental and health hazards.

KALEIDO Mumbai Office:

Kaleido works towards complete solutions that adequately successful address human, environment, and commercial issues.

7th Floor No. 704. Highway Commerce Center, IB Patel Road, Mumbai-400063

perfect center of gravity **Bengaluru Office:**

No. 23 1st Floor, VS Raju Road, Sheshadripuram, Bengaluru - 560020

Safe CPU position for rat and redent free protection of wires



Optimized and precise temperature controls for all 3 sections. (Bed, Pre & Post)



Optimised Weight Distribution,



3.3 m Wide Take up system can handle almost all type of media



SHIFT TO SUSTAINABLE QUALITY PRINTING

Print effortlessly at speed upto

2000 SQFT/HR.

KS20

HIGH-SPEED, HIGH-QUALITY SOLVENT PRINTER



LET'S START

Available in 4 & 8 heads

KM-1024i **Head Configuration**

Contact Us:

+91 9741478697 / 9820134208 / 9886786597 info@kaleidoindia.com | www.kaleidoindia.com